HP PageWide XL 4250 40-in Multifunction Printer with Top Stacker



Fast, efficient printing experience with the ultimate security¹



Fast mono and color print, keep cost under control

- Don't waste time waiting on prints-highproductivity monochrome and color speeds up to 12 D pages/min.²
- Excellent technical prints with HP PageWide XL pigment inks-vivid color, crisp lines, fine detail beat LED.³
- Save with low running costs in mono and color⁴ and with up to 10 times lower energy consumption.5
- Eco-Carton replaces plastic cartridge—80% reduction in plastic and 66% C02e reduction⁶, free take back.7

Enhanced print/scan/copy for extreme simplicity

- Easy printing and workflow efficiency with HP Click, HP SmartStream software, HP SmartTracker cost control
- The market's largest 15-inch touchscreen⁸ makes it easy to operate from the front and the back.
- Scan on the fly, gain agile digitalization with live scan preview and contextual post-edit capabilities.
- Easy collaboration—access personal/network group folders at touchscreen; print, save, and share right away.

World class printer protection with HP Wolf **Pro Security**

- Best network protection with HP Connection Inspector dynamic security, HP Secure Boot, and Whitelisting.¹
- Keep your fleet secure and set security ٠ preferences—any time—with HP Security Manager software.
- Control who accesses the printer and its confidential documents with secure user authentication.

For more information, please visit https://www.hp.com/go/pagewide-xl-4250

This printer is intended to work only with cartridges that have a new or reused HP chip, and it uses dynamic security measures to block cartridges using a non-HP chip. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. A reused HP chip enables the use of reused, remanufactured, and refilled cartridges. More at: http://www.hp.com/learn/ds

 ¹ Based on comparison of published security specifications commissioned by HP and performed by Sogeti in January, 2024. Comparison of the HP PageWide XL portfolio and competitors that represent the majority market share of LED and UV-get printers worldwide as of 2023 according to IDC. Comparison matrix and further details available upon request.
² The HP PageWide XL 4250 Multifunction Printer delivers 12 CAD output D(A1 prints in 1 minute. Number of pages will vary depending on the print mode and application printed.
³ Based on testing commissioned by HP and performed by Sogeti in September, 2020. The detail based on the number of line breaks found in 1.5 mm of line. On vertical 1 px CMXK lines. Printed on 0ce 75 g plain paper using equivalent fast/high-speed print modes. For output produced with an HP PageWide XL 8200 Printer and comparable printers from different manufacturers and that represent the majority market share of LED and UV-get printers worldwide as of 2019 according to IDC.
⁴ Calculation based on total cost of ownership comparison of comparable comparable competitive printer, considering average printend diff. Results show maintenance costs reduced by 50% when printing technical drawings. Analysis period of 5 years and assuming a production of 1000 m²/month with a printing category distribution of: 80% lines, 20% high-density images. Testing commissioned by HP and performed by Soget in September, 2020.
⁶ Based on test performed internally by HP based on ISO 20690 and performed in September, 2020. Comparable printers vising LED technology based on LED printers capable of printing 4-6 D/A1 pages per minute and which represent the majority market share of mid-volume LED share 01-LED and UV-get printers into US and 01-LED cording to IDC. as of October, 2020.
⁶ Based on 1-Litter cartridge, figures might be slightly different for 500-mi cartridge. Co20.
⁶ Based on 1-Litter cartridge, figures might be

to 147,755 km (91,811 miles) driven by an average passenger vehicle or 4,718,692 million smartphones charged. ⁷ Vish thtps://www.hp.com/recycle to see how to participate and for HP Planet Partners program availability; program may not be available in your jurisdiction. Where this program is not available, and for other consumables not included in the program, consult your local waste authorities on appropriate disposal. ⁸ Based on comparison of published front panel specifications commissioned by HP and performed by Sogeti in September, 2020. Comparison of the HP PageWide XL portfolio and competitors that represent the majority market share of LED and UV-gel printers worldwide

as of 2019 according to IDC

Datasheet | HP PageWide XL 4250 40-in Multifunction Printer with Top Stacker

Technical specifications

General

| General | |
|---------------------------------|--|
| Description | Large-format color MFP |
| Technology | HP PageWide Technology |
| Applications | Line drawings; Maps; Orthophotos; Posters |
| Ink types | Pigment-based (C, M, Y, K) |
| Ink cartridges | 4 (C, M, Y, K) |
| Cartridge size | 500 ml |
| Printheads | 8 (C, M, Y, K) |
| Average printhead life | 32 L |
| Printhead warranty | 12 months from the date of installation, or 10 L, or until the Warranty Ends date printed on the packaging, whichever comes first |
| Print resolution | 1200 x 1200 dpi |
| Minimum line width | 0.0008 in (HP-GL/2 addressable) |
| Line accuracy | ±0.1% ¹ |
| Print speed | |
| Technical documents (from roll) | Up to 650 ANSI D pages/hr, 12 ANSI D pages/min |
| Warm-up time | No warm up |
| First page out | 22 sec (from USB) |
| Media | |
| Media rolls | 2 rolls default with auto-switching, expandable to 4 rolls |
| Roll size | 11 to 40 in |
| Maximum roll diameter | Up to 7 in |
| Roll core diameter | 3 in |
| Grammage | 19 to 53 lb |
| Media thickness | Up to 15.7 mil |
| Media types | Bond and recycled papers, poster papers, polypropylene, Tyvek papers, matte film |
| Media output (standard) | Top stacker (up to 100-page capacity) |
| Scanner | |
| Description | 36-in (91-cm) CIS scanner |
| Speed | Color: up to 6 in/sec Grayscale: up to 10 in/sec |
| Optical resolution | 1200 dpi |
| Scan width | Up to 36 in |
| Original thickness | 0.01 in |
| Maximum copy length | 374.5 in |
| Maximum scan length | 164 ft (PDF), 39 ft (TIFF), 26 ft (JPEG) ² |
| Scan format | JPEG, TIFF, multi-TIFF, PDF, PDFA, multi-PDF, multi-PDFA |
| Scan features | Live preview, scan quicksets, smart background removal, black enhancement, automatic de-skew, reduce scan speed, post-edit settings (contrast, brightness, rotation, cropping and skew) |
| Scan destination | Printer storage, USB drive, network folder (SMB), My home folder, scan to email, scan to HP SmartStream software |
| Embedded controller | |
| Processor | Intel Celeron |
| Memory | 8 GB DDR4 |
| Hard drive | 500 GB HDD (AES-256 encrypted) |
| Native print languages | HP-GL/2, TIFF, JPEG, Adobe PostScript 3, Adobe PDF 1.7 |
| Remote management | HP Partner Link, HP Embedded Web Server, HP Web Jetadmin, PrintOS |
| Connectivity | |
| Interfaces | Gigabit Ethernet (1000Base-T), USB 2.0 host |
| Printing paths | HP SmartStream software (optional), HP Click printing software, HP PageWide XL print drivers (PDF, HP-GL/2, and PCL3), Apple AirPrint |
| | |
| User interface | |

| Printer | 77 x 30.9 x 55.7 in |
|-----------------------|--|
| Shipping | 88.9 x 40.9 x 62.1 in |
| Weight | |
| Printer | 996 lb |
| Shipping | 1368 lb |
| Environmental | |
| Operating temperature | 41 to 104°F |
| Operating humidity | 20 to 80% RH, depending on media type |
| Acoustics | |
| Sound pressure | \leq 60 dB(A) (operating), \leq 36 dB(A) (idle), \leq 20 dB(A) (sleep) |
| Sound power | ≤7.8 B(A) (operating), ≤5.5 B(A) (idle), ≤3.5 B(A) (sleep) |
| Power | |
| Consumption | 0.27 kW (typical); 0.7 kW (max printing); 95 W (ready); <16 W (sleep) |
| Requirements | Input voltage (auto ranging) 100-127/200-240 V (±10%), 50/60 Hz (±3 Hz), 7/3.5 A |
| Certification | |
| Safety | IEC 60950-1+A1+A2 and IEC 62368-1 2nd ed. compliant; USA and Canada (CSA listed); EU (LVD and EN 60950-1 and 62368-1 compliant); Russia, Belarus, and Kazakhstan (EAC); China (CCC) |
| Electromagnetic | Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KC) |
| Environmental | ENERGY STAR, EPEAT Registered, UL 2801 ECOLOGO, CE marking (including RoHS, WEEE, REACH). In compliance with WW RoHS materials restriction requirements in China, Korea, India, Vietnam, Turkey, Serbia, and Ukraine |
| Warranty | 90 days |

Ordering information

| 86Z39A | HP PageWide XL 4250 40-in Multifunction Printer with Top Stacker |
|------------------------------------|--|
| Accessories | |
| 2NH46AAE | HP SmartStream Document Organizer Module |
| 2NH47AAE | HP SmartStream Pixel Analysis Module |
| 6UA02AAE | HP SmartStream Workflow Management Module |
| 8SB02A | HP PageWide XL Drawer |
| 8SW00A | HP SmartStream USB Preflight Manager |
| 8SW00AAE | HP SmartStream Preflight Manager |
| 8SW03A | HP SmartStream Print Controller USB for HP PageWide XL 4000 Printer series |
| 8SW03AAE | HP SmartStream Print Controller for HP PageWide XL 4000 Printer series |
| 8SW13A | HP SmartTracker USB for HP PageWide XL 4000 Printer series |
| 8SW13AAE | HP SmartTracker for HP PageWide XL 4000 Printer series |
| 8SW21A | HP Click USB for HP PageWide XL 4000 Printer series |
| Original HP print | ing supplies |
| 3ED83A | HP 865 500-ml Magenta PageWide XL Ink Cartridge |
| 3ED84A | HP 865 500-ml Yellow PageWide XL Ink Cartridge |
| 3ED85A | HP 865 500-ml Cyan PageWide XL Ink Cartridge |
| 3ED86A | HP 864 500-ml Black PageWide XL Ink Cartridge |
| 3WW73A | HP 874/876 PageWide XL Cleaning Container |
| 3WW99A | HP 841/874/876 PageWide XL Maintenance Cartridge |
| C1Q19A | HP 841/874 PageWide XL Printhead |
| Original HP large | format printing materials |
| HP Production M HP Production S | d Paper, 3-in Core (FSC® certified) ³ (recyclable) ⁴ atte Poster Paper, 3-in Core (FSC® certified) ³ (recyclable) ⁴ atin Poster Paper, 3-in Core (FSC® certified) ³ (recyclable) ⁴ syweight Coated Paper, 3-in Core (FSC® certified) ³ (recyclable) ⁴ |

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

 1 ±0.1% of the specified vector length or ±0.2 mm (whichever greater) at 23°C (73°F), 50-60% relative humidity, on A0/E printing material in Best or Normal mode with HP Matte Polypropylene and HP PageWide XL pigment

on AO/E printing material in best or normalized and intervention of the print of th



